



About FlowFraction 1000

The FlowFrac 1000 is an X-Y-Z fraction collector designed to be sturdy, reliable, and easy to use. It provides automated sample introduction for septum and non-septum piercing applications. The FlowFrac 1000 can be used with various vial types and sizes. Additionally, the FlowFrac 1000 allows different cooling options such as Peltier+ and liquid chilling.

The FlowFrac 1000 connects to and is controlled by the Seg-Flow automated sampling system. The FlowFrac 1000 cannot operate without a Seg-Flow.

RACK HOLDER (Option 1)

- No sample temperature control
- Holds two racks or four microtiter plates

PELTIER+ (Option 2)

- Chill as low as -8°C with a single cold rack
- Chill as low as 0°C when both racks are turned on

CHILLER PLATE (Option 3)

- Primary application is for samples requiring freezing
- 4°C to -10°C
- Requires a user provided chiller/water bath
PN: 99-1240 Flownamics Chiller Box w/Connections

Specifications

Electrical

External Power Supply	Auto-sensing: 100 - 120 VAC / 220 - 240 VAC, 1.5 A (50/60 Hz)
Power Consumption	150 VA
System Requirement	24 VDC, 4.17 A

Regulatory Compliance	CE, RoHS
------------------------------	----------

Rack Sizes

- 96 well plate (192 positions)
- 5 mL (60 positions)
- 50 mL (14 positions)
- 2 mL HPLC (60 positions)
- 15 mL (30 positions)

External Device Communication Interface

USB	1 port
------------	--------

Aliquot Volumes

Sample Size	0.25 - 50 ml (user defined)
--------------------	-----------------------------

Physical

Dimensions	13.875" W	35.2 cm W
	19.25" D	48.9 cm D
	20.375" H	51.8 cm H
Weight	25.8 lb	11.7 kg

Environmental

Ambient Temperature	Operation: 18 to 28°C (64 to 82°F) Storage: -20 to 60°C (-4 to 140°F)
Relative Humidity	Operation: 20 to 80% non-condensing Storage: 10 to 80% non-condensing